

Horizontal Sterilizer PL

CE 1155 PED

PROHS Equipamento Hospitalar
e Serviços Associados, S.A.

Rua do Castanhal 316
Zona Industrial Maia I, sector II
4475-122 Maia, Portugal

| T | +351 229 059 170
| F | +351 229 015 900
| E | prohs@prohs.pt
| W | www.prohs.pt



Horizontal Sterilizer PL



PROHS Horizontal Steam Sterilizers has as basis of its function the control of the Temperature and Pressure parameters seeking the complete elimination of all living micro organisms.

Through fast and uniform heat transference, PROHS Horizontal Steam Sterilizers are an indispensable tool in places where high levels of sterilization are required.

Main Characteristics

- Totally made in AISI 316L stainless steel.
- Vertically sliding doors, with automatic command.
- Colour "Touch Screen" display, allowing a simple and intuitive interface with the sterilizer.
- Allows the identification of the user responsible based on a password.
- Water and energy saver.
- The entire control is made from the PLC (Programmable Logic Controller).
- Fast printer with graphical registers and conclusive results in real time.
- Fully customizable programs, allowing the creation of 9 solids programs and 5 liquid programs.
- Liquid Cycle with product temperature probe.

Model (Capacity litres)	Useful Dimensions (cm) (Height x Width x Depth)	External Dimensions (cm) (Height x Width x Depth)	Power (Without Steam Gen.)	Power (With Steam Gen.)
PROHS FJ 70L PL	32 x 32 x 70	170 x 77 x 92	1,3 KW	14 KW
PROHS FJ 110L PL	40 x 40 x 70	180 x 84 x 96	1,3 KW	21 KW
PROHS FJ 175L PL	50 x 50 x 70	180 x 94 x 96	1,3 KW	21 KW
PROHS FJ 250L PL	50 x 50 x 100	180 x 94 x 127	2,1 KW	32 KW
PROHS FJ 340L PL	70 x 70 x 70	195 x 116 x 96	2,1 KW	32 KW
PROHS FJ 360L PL	60 x 60 x 100	180 x 106 x 127	2,1 KW	32 KW
PROHS FJ 490L PL	70 x 70 x 100	195 x 116 x 127	2,1 KW	42 KW
PROHS FJ 640L PL	70 x 70 x 130	195 x 114 x 157	2,8 KW	53 KW
PROHS FJ 780L PL	70 x 70 x 160	195 x 114 x 187	2,8 KW	53 KW
PROHS FJ 930L PL	70 x 70 x 190	195 x 114 x 216	2,8 KW	68 KW

Certification

Directive 2014/68/UE
EN 13445:2014

Accessories

- Load Car and Platform.
- Load baskets.
- External Panels.
- Steam Generator (integrated or external)
- Silent air compressor.
- Water softner.

Connections to External Nets

- Power Supply: 3~400V-50/60Hz
- Water: 3/4" | 1 a 6 Bar ($\times 10^5$ Pa)
- Compressed Air: 3/8" | 5 a 7 Bar ($\times 10^5$ Pa)
- Steam: 1,2" | 3,5 to 5 Bar ($\times 10^5$ Pa)
- Sewer: 1,5" Heat resistant Material

Programs / Standard Cycles

- 9 Solid cycles
- 5 Liquid Cycles
- Bowie Dick (test cycle)
- Leakage test (test cycle)

